Isopropanol is a colorless, flammable liquid with a distinctive alcohol odor. Most products are completely mixed. Water-containing solvents, including acrylic and epoxy resins, ethyl cellulose, natural resins, gum, polyvinyl butyral, alkaloids and some essential oils

Recommended use	For surface cleaning of bonding surfaces (GLASS, painted body, etc.) using adhesives for automotive glass and primer

Physical Properties

Physical properties		
	Molecular Weight	60.10
	Relative Evaporation Rate nBuAc=1	2.9
	Vapor Pressure at 20°C, mmHg	33.1
	Density at 20°C lb/gal	6.55
	Specific Gravity at 20/20°C	0.787
	Viscosity at 20°C cP	2.4
	Surface Tension (dynes/cm at 20°C)	21.4
	(dynes/cm at 25°C)	-
	Hansen Solubility Parameters Total	11.5
	Non-Polar	7.7
	Polar	3.0
	Hydrogen Bonding	8.8
	Boiling Point, °C at 760mm Hg	82.3
	Solubility at 20°C %Wt In Water	100
	%Wt Water in	100
	Closed Cup Flash Point °F	53
	SARA 313 (see note 1†)	Y
	Hazardous Air Pollutant (see note 2††)	N

Application details

Manual	Before use, wipe clean with a certain amount subdivided enough to moisten the surface of a brush, sponge, felt, or the like. Make sure that the primer is completely dried before applying Primer.

Storage and package

Shelf life	Keep one year unopened
Storage	Store in cool room without direct sunlight (below 25 ℃)
Packing Unit	Tin cans (1L, 4L, 18L) can be packed

Remarks

Handling Precautions	After opening, please make sure that it is completely sealed so that moisture is not absorbed (it will be exhausted within 1 month after opening).
1'st issue	2017-01-02
Revision	2017-01-02